


M16 SHCS - AS1110 Class 12.9 Zinc Plated

Bolt Shear Capacity 'Thread' [BSC] = 94kN
 Bolt Pattern Shear Capacity [BPSC] = 71,628 Nm
 Bolt Pattern Design Torque [BPDT] = 17,907 Nm


$$BDPT = \frac{1}{4} \times BPSC$$

IFC-8100-95 Coupling Ratings:
 Intermediate = 10,275 Nm
 Continuous = 6,850 Nm


IFC-8100-95 Coupling Weight = 7.4 kg




Item 2: M16 x 65 SHCS, Nut and Spring Washer



Item 3: M16 x 50 SHCS and Spring Washer



Optional T-bush Kit
 Part Number: TBush Kit 7/8 (ZP) 8 bolt



IFC-8100-95

Copyright © 2021 Isoflex Technologies Pty Ltd				
TITLE		IFC8100-95 General Arrangement		
	NAME	DATE		
DRAWN	Matthew McCart	01/Sep/21		
CHECKED	-	-		
APPR	-	-		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS		SIZE	DWG NO	REV
		A3	IFC8100-95	B2
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE		FILE NAME: IFC8100-95 General Arrangement_B2.dft		
SCALE: 1:2	WEIGHT:	SHEET 1 OF 1		

