

3/8" UNF Bolt - AS2465 Grade 5 Zinc Plated

Bolt Shear Capacity 'Thread' [BSC] = 27kN
 Bolt Pattern Shear Capacity [BPSC] = 16,800 Nm
 Bolt Pattern Design Torque [BPDT] = 5,600 Nm

$BDPT = \frac{1}{3} \times BPSC$

IFC-81610-HT Coupling Ratings:
 Intermediate = 5,500 Nm
 Continuous = 3,700 Nm


IFC-81610-HT Coupling Weight = 2.2 kg

IFC-81610-HT

Flexible Coupling to suit
 K56.2.GB99 1610 bolt pattern


 Item 2: 3/8" UNF x 1 3/4" Hex Head Bolt, Nut and Spring Washer


 Item 3: 3/8" UNF x 1 1/4" Hex Head Bolt and Spring Washer



Copyright © 2020 Isoflex Technologies Pty Ltd				
TITLE		IFC81610-HT General Arrangement		
	NAME	DATE		
DRAWN	Matthew McCart	09/Sep/20		
CHECKED	-	-		
APPR	-	-		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS		SIZE	DWG NO	REV
		A3	IFC81610-HT	B1
FILE NAME: IFC81610-HT General Arrangement_B1.dft				
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE		SCALE: 1:2	WEIGHT:	SHEET 1 OF 1

