

M16 SHCS - AS2465 Grade 8 Zinc Plated

Bolt Shear Capacity 'Thread' [BSC] = 94kN
 Bolt Pattern Shear Capacity [BPSC] = 75,200 Nm
 Bolt Pattern Design Torque [BPDT] = 18,800 Nm


$$BDPT = \frac{1}{4} \times BPSC$$

IFC-8400-95 Coupling Ratings:
 Intermediate = 10,500 Nm
 Continuous = 7,000 Nm

IFC-8400-95 Coupling Weight = 6.4 kg




Item 2: M16 x 65 SHCS, Nut and Spring Washer



Item 3: M16 x 50 SHCS and Spring Washer

IFC-8400-95



Copyright © 2019 Isoflex Technologies PTY Ltd			
TITLE		IFC8400-95 General Arrangement	
	NAME	DATE	
DRAWN	Matthew McCart	03/Sep/20	
CHECKED	-	-	
APPR	-	-	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS		SIZE	DWG NO
DRAWING NOT TO SCALE SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE		A3	IFC8400-95
		REV	B1
FILE NAME: IFC8400-95 General Arrangement_B1.dft		SCALE:	WEIGHT:
		SHEET 1 OF 1	

