

7/8" UNC Bolt - AS2465 Grade 8 Zinc Plated

Bolt Shear Capacity 'Thread' [BSC] = 175kN
 Bolt Pattern Shear Capacity [BPSC] = 210,000 Nm
 Bolt Pattern Design Torque [BPDT] = 52,500 Nm

$$BDPT = \frac{1}{4} \times BPSC$$

IFC-8900-95 Coupling Ratings:

Intermediate = 27,500 Nm

Continuous = 18,300 Nm


Permissible Power Loss = 250 W

Maximum Rotation Speed = 2,000 RPM

IFC-8900-95 Coupling Weight = 25.0 kg




Item 2: 7/8" UNC x 3 1/2" Hex Head Bolt, Nut and Spring Washer



Item 3: 7/8" UNC x 2 1/2" Hex Head Bolt and Spring Washer

IFC-8900-95



Copyright © 2020 Isoflex Technologies Pty Ltd				
TITLE		IFC8900-95 General Arrangement		
	NAME	DATE		
DRAWN	Matthew McCart	09/Sep/20		
CHECKED	-	-		
APPR	-	-		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS		SIZE	DWG NO	REV
		A3	IFC8900-95	B1
FILE NAME: IFC8900-95 General Arrangement_B1.dft				
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE		SCALE: 1:4	WEIGHT:	SHEET 1 OF 1

